





LDC LP No. 10/2024-25 Dtd: 15th October 2024

List of Products Covered in Our LDC LP
Project Wires (200-300 Mtrs.)
Single Core Flexible Cables
Multicore Flexible Cables
Single Core XLPE Unarmoured/Armoured Cables
Solar Cables
BMS Cables
Braided Cables
Steel Braided Cables
Welding Cables
Aluminium Service Wires
Festoon Cables
Uninyvin Cables









LDC LP No. 10/2024-25 Dtd: 15th October 2024

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES.FLAME RETARDANT LEAD FREE (FRLF) / FLAME RETARDANT LOW SMOKE (FRLSH) / HEAT RESISTANT FLAME RETARDANT LOW SMOKE HALOGEN - LEAD FREE CONFORMING TO IS- 694:2010 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

POLYCAB PVC INSULATED SINGLE
CORE UNSHEATHED INDUSTRIAL
(MULTISTRAND) CABLES – HALOGEN
FREE FLAME RETARDANT (HFFR)
WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR
FOR VOLTAGE GRADE 1100 VOLTS

Size	FRLF	FRLS-H	GREEN WIRES HR-FRLS-H-LF	HFFR	Coils Per Box
(sq.mm.)	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)				
0.75	5635	5810	5915	6120	10
1	7395	7610	7735	7930	8
1.5	10880	11205	11360	11690	6
2.5	17650	18190	18455	18990	4
4	18150	18700	18965	19525	4
6	27140	27960	28380	29190	3
10	47560	48950	49670	51080	1
16	75400	77615	78755	81000	1

NOTES:

- 1. The above rates are exclusive of GST which shall be charged extra.
- 2. This Price List is subject to change without notice.
- 3. As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.









LDC LP No. 10/2024-25 Dtd: 15th October 2024

Polycab FR PVC Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:2010 with Bright Annealed Copper Conductor for Voltage Grade 1100 Volts

Nominal Area of	Number/ Nom.	Current Carrying	(Price in F	Rs./100m)
Conductor (sq mm)	Conductor (No./dia mm)	Capacity (Amps)	Single Core	Packing
0.5	16/.2	5	1365	24
0.75	24/.2	8	1910	24
1	32/.2	13	2435	20
1.5	30/.25	17	3515	16
2.5	50/.25	24	5780	12
4	56/.3	30	8880	8
6	84/.3	38	13250	6
10	80/.4	52	23300	1
16	126/.4	70	36300	1
25	196/.4	88	57100	1
35	276/.4	110	79900	1
50	396/.4	145	114000	1
70	354/.5	215	161100	1
95	484/.5	260	212600	1
120	608/.5	305	274000	1
150	750/.5	355	343000	1
185	925/.5	415	426800	1
240	1210/.5	500	557000	1
300	1527/.5	585	696900	1
400	2036/.5	695	928600	1
500			1161600	1
630			1498400	1

Polycab PVC Insulated and PVC Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Flexible Cables for Voltage Grade 1100 Volts conforming to IS: 694:2010

(Price in Rs./100m)										
2 Core	3 Core	4 Core	2 - 4 Core Packing	5 Core	6 Core					
3555	4870	6230	5	7825	9375					
4750	6600	8480	5	11100	13300					
6040	8395	10850	5	14325	17100					
8215	11670	15275	5	19475	23700					
13300	18650	24700	4	31950	38200					
19900	28700	37700		50400	60400					
29300	42300	55600		74200	89000					
50100	72900	96400		127900						
78400	114600	151300		196200						
130600	190100	248300		356700						
181800	264100	347100		488700						
258200	376200	496800		707300						
366800	521800	689800		967100						

Polycab PVC Insulated, PVC Round Sheathed Multi Core Industrial Flexible Cables conforming to IS 694:2010 with Bright Annealed Copper Conductor for **Voltage Grade 1100 Volts** Price in Rs./100 Mtrs. **Nominal Area of** Number/ Nom. Dia of **Current Carrying** Conductor (sq mm) Conductor (No./dia mm) Capacity (Amps) 7 Core 8 Core 10 Core 12 Core 10500 12600 18150 15600 0.5 16/.2 0.75 24/.2 15050 17700 21950 25800 32/.2 19200 22700 28000 33100 30/.25 50/.25 27000 31000 39250 46400 24 64400 43700 52200 77500 56/.3 72400 Number/ Nom. Dia of Price in Rs./100 Mtrs. Nominal Area of **Current Carrying** Conductor (No./dia Conductor (sq mm) Capacity (Amps) 14 Core 16 Core 19 Core 24 Core mm) 16/.2 23800 27700 34900 0.5 20900 30000 24/.2 34200 40100 50100 0.75 8 38800 44100 51700 65000 32/.2 13 54900 63400 73300 89400 102300 118700 153400









LDC LP No. 10/2024-25 Dtd: 15th October 2024

	Polycab Multi Strand Bare Copper conductor XLPE insulated PVC Sheathed Cables											
Nominal Area	No/Dia of Strands	Current rating in Air at 40°C	Cu Conductor Unarmoured Cables	Cu Conductor Aluminium Armouring Cables								
mm²	No/mm		Rs/100 Mtr.	Rs/100 Mtr.								
6	84/0.3	55	18300	24900								
10	80/0.4	75	30800	41900								
16	126/0.4	103	45600	53300								
25	196/0.4	126	72700	81200								
35	276/0.4	152	99800	109600								
50	396/0.4	189	139300	152500								
70	354/0.5	240	191300	210000								
95	484/0.5	297	260100	270800								
120	608/0.5	346	328700	342000								
150	750/0.5	390	410500	427700								
185	925/0.5	460	501300	516200								
240	1210/0.5	552	651500	679900								
300	1527/0.5	640	812100	854800								
400	2036/0.5	753	1083300	1133600								

Polycab FRLS PVC Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:2010 with Bright Annealed Copper Conductor for Voltage Grade 1100 Volts

Nominal	Number/ Nom.	Current	(Price in R	ts./100m)
Area of Conductor (sq mm)	Dia of Conductor (No./dia mm)	Carrying Capacity (Amps)	Single Core	Packing
0.5	16/.2	5	1400	24
0.75	24/.2	8	1965	24
1	32/.2	13	2470	20
1.5	30/.25	17	3545	16
2.5	50/.25	24	5870	12
4	56/.3	30	8940	8
6	84/.3	38	13415	6
10	80/.4	52	23800	1
16	126/.4	70	36900	1
25	196/.4	88	57800	1
35	276/.4	110	80800	1
50	396/.4	145	115100	1
70	354/.5	215	162900	1
95	484/.5	260	214900	1
120	608/.5	305	276400	1
150	750/.5	355	346500	1
185	925/.5	415	430700	1
240	1210/.5	500	562500	1
300	1527/.5	585	704000	1
400	2036/.5	695	937900	1
500			1173300	1
630			1513300	1

Polycab PVC Insulated and FRLS Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Flexible Cables for Voltage Grade 1100 Volts conforming to IS: 694:2010

	(Price in Rs./100m)										
2 Core	3 Core	4 Core	2 - 4 Core Packing	5 Core	6 Core						
3780	5090	6455	5	8000	9555						
5035	6865	8755	5	11300	13625						
6310	8695	11140	5	14550	17500						
8555	12025	15530	5	19900	24200						
13800	19100	25200	4	32400	39200						
20500	29300	38400		51300	61400						
30000	43000	56200	75600		90700						
51000	74000	97800		130400							
80400	117200	154200	154200								
133300	193800 253400			363600							
185600	269300	354500		498300							
263500	383700	506500		721300							
374100	532100	703700		986400							
	754300	995100									
	957700	1264100									
	1197200	1580300									
	1474400	1948800									
	1903300	2519400									
	2375000	3145000									
	3164500	4165800									









A B Pal Electricals (P) Limited

Price List

LDC LP No. 10/2024-25 Dtd: 15th October 2024

Polycab PV		Round Sheathed I ght Annealed Copp				o IS 694:2010			
Nominal Area of Number/ Nom. Dia Price in Rs./100 Mtrs.									
Conductor (sq mm)	of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	7 Core	12 Core					
0.5	16/.2	5	10700	12700	15800	18600			
0.75	24/.2	8	15250	17900	22500	26200			
1	32/.2	13	19800	23000	28650	33900			
1.5	30/.25	17	27300	31500	40100	47200			
2.5	50/.25	24	44900	53300	65500	78700			
4	56/.3	30	74000						
Nominal Area of	Number/ Nom.	Current Carrying	Price in Rs./100 Mtrs.						
Conductor (sq mm)	Dia of Conductor (No./dia mm)	Capacity (Amps)	14 Core	16 Core	19 Core	24 Core			
0.5	16/.2	5	21325	24300	28100	35500			
0.75	24/.2	8	30750	34700	41000	51200			
1	32/.2	13	39450	45000	52900	66300			
1.5	30/.25	17	55900	64400	74800	95800			
2.5	50/.25	24	91400	104400	121000	156700			

	POLYCAB SOLAR CABLES									
Flexible Tinned Copper Cond Beam) LSZH Insulation/ Cross Sheathed Solar Cable	linkable (E Beam) LSZH	Multistrand, Cr Smoke Insula Smoke Sheathin	copper Conductor Single Core ss Linked, Zero Halogen Low tion and Cross Linked Low g , Heat Resistant upto 120°C lesistant Solar Cables							
Size in Sq.mm.	Price in Rs./100 Mtr.	Size in Sq.mi	n. Price in Rs./100 Mtr.							
2.5	7565	2.5	7055							
4	10825	4	10200							
6	15825	6	15100							
10	27450									
16	44300									
25	70400									









A B Pal Electricals (P) Limited

Price List

LDC LP No. 10/2024-25 Dtd: 15th October 2024

		POLYCA	AB BUILDING	MANAGEMI	ENT SYSTEM	CABLES (BMS)
Flexible E	Bare Copper Condu	ctor, PVC Insulated,Cr	oss Laid Up, Overall	Aluminium Mylar Rs./100n	•	g with ATC Drain Wire PVC Outer Sheath BMS Cables (Price
Cores	0.5 sq.mm	0.75 sq.mm	1.0 sq.mm	1.5 sq.mm	2.5 sq.mm	
2	5945	7600	9130	11900	18600	
3	7375	10010	12100	16100	25700	
4	9130	12100	15500	20700	32500	
5	11250	15100	18400	25100	41100	
6	13000	17100	21400	30300	49200	
7	14200	20100	24900	34000	58300	
8	16100	21700	27700	38100	65000	
10	19100	26900	34000	47100	79500	
12	22600	31500	40200	55800	97500	1
14	26300	36800	46500	64200		1
16	29700	41300	52300	74100		1
19	34000	49200	61800	86200		1
24	42300	60400	76500	110000		1

NOTES:

Packing - 100/300 Mtrs. Coils & 2000 Mtrs. Drums

- 4% Extra Charges for Drum Packing

Polycab Annealed Bare Cu Flexible Conductor PVC Insulated, Tinned Cu Braided (Screened) PVC Sheathed Flexible Unarmoured Cables 1100 Volts. (Price in Rs./100 Mtr)												
Cores	0.5 Sq mm.	0.75 Sq mm.	1.0 Sq mm.	1.5 Sq mm.	2.5 Sq mm.	4 Sq mm.	6 Sq mm.	10 Sq mm.	16 Sq mm.	25 Sq mm.	35 Sq mr	
2	10900	13400	15100	18300	27700	37900	53300					
3	12600	16300	20400	25300	37000	58300	81500	123400	186800	351700	461700	
4	15700	20400	24900	31000	46700	71200	99200	166100	268000	424000	587100	
5	19900	24500	28100	37600	62800				,			
6	21100	27700	32500	44100	70400							
7	22700	31900	37000	g48800	79600							
8	26400	37900	42100	56300	83100							
10	33500	41800	56000	70600	92900							
12	37900	47300	60000	79600	108600							
14	41800	56000	70400	95300	130600							
16	44800	65200	79100	105200	153700							
19	53300	77200	93300	130600	198500							
24	64400	86300	117100	160000	248800							









LDC LP No. 10/2024-25 Dtd: 15th October 2024

POLYCAB MULTICORE STEEL BRAIDED CABLES													
Flex Bare Copper Condutor, PVC Insulated, Cores Laid Up Together PVC Inner Sheathed, GI Wire Braided (Flexible Armouring), Overall PVC Sheathed Steel Braided Cables. (Price in Rs./100 Mtr.)													
Sieci States Gastes (Tite III 13) 200 Intri													
Cores	0.5 Sq.mm.	0.75 sq.mm	1.0 sq.mm	1.5 sq.mm	2.5 sq.mm	4 sq.mm	6 sq mm						
2	11500	13900	15500	19400	27800	39300	54600						
3	14000	17000	19600	25200	37400	55600	76200						
4	16500	20900	24300	31500	47500	69300	99100						
5	19400	24700	29600	38500	57400								
6	22000	28700	34000	44600	67800								
7	23900	31400	37600	49800	76200								
8	27200	35500	42500	57300	87600								
10	33200	43600	52500	70000	108500								
12	37700	50600	60500	81600	126900								
14	42900	57400	69300	94100	146000								

Cores	10 Sq.mm.	16 Sq.mm.	25 Sq.mm.	35 Sq.mm.	50 Sq.mm.	70 Sq.mm	95 Sq.mm.
2	89400	133700	202700	276400	392500	538600	720000
3	125800	189200	290900	398000	566100	781700	1046100
4	164200	248300	382900	525100	746500	1031600	1382500

NOTES:

- 3% Extra Charges for Drum Packing

POLYCA	POLYCAB INDUSTRIAL COPPER WELDING CABLES				
Polycab F	Polycab Flexible Copper Conductor 1100 Volts Welding Cable				
Nominal Area of Conductor (sq mm)	Current Carrying Capacity	Conductor Constn. Strands/ Dia in mm	HOFR Insulation Price/100m (Rs)		
16	120	509/0.2	44800		
25	160	796/0.2	70100		
35	230	1115/0.2	96800		
50	400	703/0.3	137500		
70	600	999/0.3	194400		
95	700	1346/0.3	256100		
120	1100	1699/0.3	327700		









LDC LP No. 10/2024-25 Dtd: 15th October 2024

POLYCAB SINGLE CORE PVC INSULATED 1100 VOLTS SOLID ALUMINIUM CONDUCTOR WIRES AS PER IS 694

POLYCAB PVC INSULATED AND SHEATHED TWIN CORE_FLAT & THREE CORE ROUND CABLES 1100 VOLTS EACH CORE HAVING SINGLE SOLID ALUMINIUM CONDUCTOR SERVICE CABLES AS PER IS 694

Size in Sq.mm.	Price in Rs./100 Mtr.
1.5	1385
2.5	2195
4	3115
6	4265
10	7140
16	10365
25	16120
35	21995
50	24960
70	32800
95	58200
	_

No. of Cores	Sq.mm.	Price in Rs./100 Mtr.
2 Core	2.5	7605
2 Core	4	10150
2 Core	6	13475
2 Core	10	19600
2 Core	16	28450
3 Core	2.5	11235
3 Core	4	14700
3 Core	6	17200
3 Core	10	31900
3 Core	16	42500
4 Core	2.5	13700
4 Core	4	19100
4 Core	6	27200
4 Core	10	40100
4 Core	16	53100









LDC LP No. 10/2024-25 Dtd: 15th October 2024

			FESTOON CAB	LES		
Cores	0.5 Sq.mm.	0.75 Sq.mm.	1 Sq.mm.	1.5 Sq.mm.	2.5 Sq.mm.	4 Sq.mm.
3	84	103	130	171	281	429
4	109	141	170	233	369	575
5	153	199	252	323	514	769
6	181	243	301	384	617	930
7	207	274	346	444	719	1079
8	242	315	393	512	826	1236
9	278	369	461	587	952	1410
10	307	405	506	651	1052	1573
12	361	482	603	770	1254	1879
14	436	568	708	919	1475	2204
16	492	650	817	1043	1689	2523
18	546	715	916	1171	1876	2805
24	741	972	1240	1419	2525	3796

*(Rate in Rs. Per Mtr.)









LDC LP No. 10/2024-25 Dtd: 15th October 2024

UNINYVIN CABLES

Multistranded Annealed Tinned Copper Conductor 105° C PVC Insulation with Nylon Braiding with Lacquer Coating Uninyvin Cables

Cable Size	Nom. Conductor Area (Sq.mm.)	Price in Rs./Mtr.	
22	0.347	29.60	
20	0.556	38.00	
18	0.966	56.20	
16	1.17	66.80	
14	2.05	103.00	
12	3.22	148.00	
10	5.33	211.00	
8	8.76	327.00	
6	13.30	485.00	
4	21.50	768.00	
2	33.30	1174.00	
1	40.70	1421.00	
0	53.00	1846.00	
00	68.30	2350.00	
000	84.20	2912.00	
0000	109	3745.00	

