

ISO:9001:2015, IATF:16949:2016
ISO:14001:2015, ISO:45001:2018,
ISO:50001:2011, RoHS2 Compliant,
Sedex/Smeta, G.C. Mark, Trusted Product,
TUV For Fire Survival Cable

Plant-1 : A 115 RIICO Industrial Area, Phase-1, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)

Plant-2 : A 6A, Kaharani Industrial Area, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)

E Mail : marketing@bontoncablesindia.com, Phone No. - 8130299001

Bonton Single Core Copper Conductor PVC Cables (Unsheathed)-HRFR

1100V Grade Conforming to IS:694

Nominal Area of Conductor sq.mm	HRFR PVC		Std. Pkg. of Coil in Master Carton	HRFR PVC In Project Packing	
	PartNo.	MRP (90 Mtr. Box)		PartNo.	MRP (180 Mtr. Coil)
0.75	110266N	1450	20	110266P	3605
1	110267N	1870	20	110267P	4325
1.5	110268N	2765	16	110268P	6345
2.5	110269N	4440	12	110269P	10315
4	110270N	6520	8	110270P	15655
6	110271N	9840	4	110271P	23395

Standard Packing : 90mtr. In Carton* Project Packing: 180 mtrs. Polywrapped

Colour Available : Red, Yellow, Blue, Black, White, Green & Grey

Bonton Single Core Copper Conductor PVC Insulated Cables (Unsheathed) - FRLS(H)

1100V Grade Conforming to IS:694

Nominal Area of Conductor sq.mm	FRLS(H) PVC		Std. Pkg. of Coil in Master Carton	FRLS(H) PVC in Project Packing	
	Part No.	MRP (90 Mtr. Box)		Part No.	MRP (180 Mtr. Coil)
0.75	110266NLS	1525	20	110266PLS	3785
1	110267NLS	1965	20	110267PLS	4540
1.5	110268NLS	2905	16	110268PLS	6665
2.5	110269NLS	4665	12	110269PLS	10830
4	110270NLS	6845	4	110270PLS	16435
6	110271NLS	10335	4	110271PLS	24565

Standard Packing : 90mtr. In Carton * Project Packing : 180 mtrs. Polywrapped

Colour Available : Red, Yellow, Blue, Black, White, Green & Grey

Bonton Single Core Copper Conductor ZHFR Insulated Cables - ZHFR

1100V Grade Conforming to IS:17048 (Unsheathed)

Nominal Area of Conductor sq.mm	ZHFR		Std. Pkg. of Coil in Master Carton	ZHFR in Project Packing	
	Part No.	MRP (90 Mtr. Box)		Part No.	MRP (180 Mtr. Coil)
0.75	110267NZ	1880	20	110267PZ	4035
1	110267NZ	2445	20	110267PZ	4845
1.5	110268NZ	3590	16	110268PZ	7105
2.5	110269NZ	5780	12	110269PZ	11555
4	110270NZ	8460	4	110270PZ	17535
6	110271NZ	12805	4	110271PZ	26200

Standard Packing for ZHFR : 90mtr. In Carton * Project Packing : 180 mtrs. Polywrapped

Colour Available : Red, Yellow, Blue, Black & Green

Bonton Single Core Copper Conductor PVC Cables (Unsheathed) - HRFR

1100V Grade Conforming to IS:694

Nominal Area of Conductor sq.mm	HRFR PVC		Nominal area of Conductor sq.mm	HRFR PVC	
	Part No.	MRP (100 mtr.)		Part No.	MRP (100 mtr.)
10	110272H	22030	120	110279H	271295
16	110273H	35505	150	110280H	336295
25	110274H	55325	185	110281H	415225
35	110275H	76985	240	110282H	540970
50	110276H	108915	300	110283H	674650
70	110277H	152935	400	110284H	898225
95	110278H	208600	500	110285H	1190135

Standard Packing : 100 mtrs. Coils

Colour available : Red, Yellow, Blue, Black & Green

* FRLS(H) insulation: 5% Extra

* HFLS (Halogen Free Insulation) : 12% Extra

ISO:9001:2015, IATF:16949:2016
 ISO:14001:2015, ISO:45001:2018,
 ISO:50001:2011, RoHS2 Compliant,
 Sedex/Smeta, G.C. Mark, Trusted Product,
 TUV For Fire Survival Cable

Plant-1 : A 115 RIICO Industrial Area, Phase-1, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)

Plant-2 : A 6A, Kaharani Industrial Area, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)

E Mail : marketing@bontoncablesindia.com, Phone No. - 8130299001

Bonton Single Core Copper Conductor PVC Cables (Unsheathed) - HRFR & FRLSH

1100V Grade Conforming to IS : 694

Nominal Area of Conductor sq.mm	HRFR PVC in Project Packing		FRLSH PVC in Project Packing	
	Part No.	MRP (200 mtr. Coil)	Part No.	MRP (200 Mtr. Coil)
0.5	110265 T	2665	110265 TLS	2795
0.75	110266 T	3480	110266 TLS	3655
1	110267 T	4585	110267 TLS	4815
1.5	110268 T	6720	110268 TLS	7055
2.5	110269 T	10920	110269 TLS	11465
4	110270 T	16570	110270 TLS	17400
6	110271 T	24765	110271 TLS	26005

Colour available : Red, Yellow, Blue, Black, White, Green & Grey

Bonton Jelly Flooded Aluminium Foil & Aluminium Wire Braided Co-Axial Cables

Size	Part No.	100 Meter Unarmoured	305 Meter Unarmoured	1000 Meter Armoured
RG 59	110086	3300	9865	
RG 6	110087	4135	12400	117740
RG 11	110088	8990	27195	179855

Bonton PVC insulated Telephone Cables for Indoor application conforming to TEC Specification G/WIR06/02

No. of Pair (0.40mm)	Part No.	MRP - 100 Mtr. (0.40 mm)	No. of Pair (0.50 mm)	Part No.	MRP - 100 Mtr. (0.50 mm)	No. of Pair (0.61 mm)	Part No.	MRP - 100 Mtr. (0.61 mm)
1	110082	1135	1	110091	1495	1	110101	2195
2	110083	1965	2	110092	2485	2	110102	4180
3	110084	2545	3	110093	3745	3	110103	6250
4	110085	3250	4	110094	4955	4	110104	8425
5	110086	4205	5	110095	5895	5	110105	10465
10	110087	8510	10	110096	12030	10	110106	21675
20	110088	17015	20	110097	23925	20	110107	42410
50	110089	-	50	110098	58370	50	110108	103545
100	110090	-	100	110099	122785	100	110109	207165

Bonton Multi Core Copper Conductor PVC Cables (Sheathed) - HRFR

1100V Grade Conforming to IS : 694

Nominal Area of Conductor sq.mm	Part No.	2 Core	Part No.	3 Core	Part No.	4 Core	Part No.	5 Core
0.5	110308 2C	3745	110308 3C	4985	110308 4C	6225	110308 5C	8135
0.75	110309 2C	5120	110309 3C	6770	110309 4C	8550	110309 5C	11195
1	110310 2C	6265	110310 3C	8485	110310 4C	10940	110310 5C	14285
1.5	110311 2C	8295	110311 3C	11530	110311 4C	15320	110311 5C	20110
2.5	110312 2C	13360	110312 3C	18280	110312 4C	24565	110312 5C	31865
4	110313 2C	19985	110313 3C	28335	110313 4C	37345	110313 5C	51290
6	110314 2C	29235	110314 3C	41700	110314 4C	54370	110314 5C	74925
10	110315 2C	49690	110315 3C	71165	110315 4C	93185	110315 5C	127350
16	110316 2C	78930	110316 3C	113525	110316 4C	148245	110316 5C	197470
25	110317 2C	127220	110317 3C	181480	110317 4C	238905	110317 5C	321940
35	110318 2C	175535	110318 3C	252620	110318 4C	330260	110318 5C	445270
50	110319 2C	251360	110319 3C	356670	110319 4C	470175	110319 5C	647290
70	110320 2C	350145	110320 3C	496885	110320 4C	661345	110320 5C	892810

Standard Packing : 100 mtrs. Coil

* FRLS(H) insulation : 5% Extra
 * HFLS (Halogen Free Insulation) : 12% Extra



ISO:9001:2015, IATF:16949:2016
 ISO:14001:2015, ISO:45001:2018,
 ISO:50001:2011, RoHS2 Compliant,
 Sedex/Smeta, G.C. Mark, Trusted Product,
 TUV For Fire Survival Cable

Price List w.e.f. 18th November 2024

BONTON CABLES (INDIA) PVT. LTD.



Plant-1 : A 115 RIICO Industrial Area, Phase-1, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)

Plant-2 : A 6A, Kaharani Industrial Area, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)

E Mail : marketing@bontoncablesindia.com, Phone No. - 8130299001

Bonton PVC Insulated and Sheathed 3 Core Flat Submersible Cable 1100V grade conforming to IS : 694/1990

Nominal area of Conductor sq.mm	Part Number	MRP - Per 100 Mtrs.
1.5	110311 3C FT	12435
2.5	110312 3C FT	20685
4	110313 3C FT	29600
6	110314 3C FT	43035
10	110315 3C FT	72630
16	110316 3C FT	112430
25	110317 3C FT	181040
35	110318 3C FT	251985

Bonton PVC Insulated and sheathed 4 Pair Twisted LAN Cable

Size	MRP 305 Meter
CAT 6	15430

Flexible Bare Copper Conductor PVC Insulated Overall Aluminium Mylar Tape Shielded along with ATC Drain wire PVC Outer Sheath Aluminium Mylar Tape Wires / Cables (100 Mtr Coil)

Core	0.5 sq.mm	0.75 sq.mm	1.0 sq.mm	1.5 sq.mm	2.5 sq.mm
2	7255	9365	9875	12720	19755
3	9275	11895	13315	17365	27465
4	11285	14510	16770	22255	36635
5	11050	17360	20205	27125	43395
6	15340	20215	23890	32470	52085
7	17025	22835	26875	36275	58840
8	19630	25680	30320	41355	67175
10	24020	31845	37235	51475	84155
12	27960	36850	43985	60630	99265
14	31870	43145	51125	70130	115075
16	35645	48530	57665	79650	130745
19	41945	56480	67530	93300	154295
24	52070	71100	84760	118275	194365

Note : 3% Extra Charges for Drum packing

FIRE SURVIVAL CABLE

Bonton Multicore High Performance Silicon Rubber (HPSR) Insulated LSZH Sheathed Fire Survival Cable - TUV Certified Cable

Test as per BS6387 C.W.Z.

Size	Part No.	MRP - Per Mtr (Un-armoured)	MRP - Per Mtr (Armoured)
2 Core x 1.5 sq.mm	110331	320	365
3 Core x 1.5 sq.mm	110332	390	435
2 Core x 2.5 sq.mm	110333	435	455
3 Core x 2.5 sq.mm	110334	520	570

Bonton MICA Tape Multicore XLPE Insulated LSZH sheathed Copper Armoured Fire Survival Cable - TUV Certified Cable

Test as per BS6387 C.W.Z.

Size	Part No.	MRP- Per Mtr.
2 Core x 1.5 sq.mm	110341	280
3 Core x 1.5 sq.mm	110342	355
2 Core x 2.5 sq.mm	110343	395
3 Core x 2.5 sq.mm	110344	495

Terms & Conditions : -

1. GST @ 18% Extra on Copper Flexible PVC Insulated Wire & PVC Insulated/Sheathed Cable (HSN Code 85446020)
2. Order are accepted subject to availability of stocks.
3. Conductor Resistance as per IS 694 is the governing criteria.

A B Pal Electricals (P) Limited

Regd. Office: 1826, Bhagirath Palace, Chandni Chowk, Delhi-110006, India
Tel.: +91-11-43-111-333, 2386-5954, 3622, 4081, 8081, **Mob.:** +91-98914-98555
E-Mail: contact@abpal.com, **Website:** www.abpal.com

