

POLYCAB

IDEAS. CONNECTED.

**A B Pal Electricals (P) Limited****Price List**

LDC LP No. 10/2024-25 Dtd : 15th October 2024

Polycab PVC Insulated, PVC Round Sheathed Multi Core Industrial Flexible Cables conforming to IS 694:2010 with Bright Annealed Copper Conductor for Voltage Grade 1100 Volts

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Price in Rs./100 Mtrs.			
			7 Core	8 Core	10 Core	12 Core
0.5	16/.2	5	10500	12600	15600	18150
0.75	24/.2	8	15050	17700	21950	25800
1	32/.2	13	19200	22700	28000	33100
1.5	30/.25	17	27000	31000	39250	46400
2.5	50/.25	24	43700	52200	64400	77500
4	56/.3	30	72400			

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Price in Rs./100 Mtrs.			
			14 Core	16 Core	19 Core	24 Core
0.5	16/.2	5	20900	23800	27700	34900
0.75	24/.2	8	30000	34200	40100	50100
1	32/.2	13	38800	44100	51700	65000
1.5	30/.25	17	54900	63400	73300	93700
2.5	50/.25	24	89400	102300	118700	153400

COAXIAL CABLE	
	305M UNARMoured
RG 59	7210
RG 6	9085
RG 11	20700
RG 6 CCS	5850
RG 11 CCS	11800

TELEPHONE CABLE	
	0.5MM - 90MTR
1 PAIR	985
2 PAIR	1755
3 PAIR	2595
4 PAIR	3430
5 PAIR	4255
10 PAIR	8270
20 PAIR	15965

SPEAKER WIRE	
	90 MTR
0.5 SQ MM	1990
0.75 SQ MM	2885
1 SQ MM	3565
1.5 SQ MM	5300
2 SQ MM	8200
2.5 SQ MM	8800

OFC CABLE	
	SALE PRICE
6F SM UNITUBE ARMoured OFC CABLE	24
8F SM UNITUBE ARMoured OFC CABLE	27
12F UNITUBE ARMoured OFC CABLE	28

CCTV CABLE (90 MTR)	
CCTV 3+1	3880
CCTV 4+1	4220

LINE CABLE	
CAT 6 FTP FR PVC	12930



POLYCAB

IDEAS. CONNECTED.

**A B Pal Electricals (P) Limited****Price List**

LDC LP No. 10/2024-25 Dtd : 15th October 2024

Polycab FRLS Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:2010 with Bright Annealed Copper Conductor for Voltage Grade 1100 Volts					Polycab PVC Insulated and FRLS Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Flexible Cables for Voltage Grade 1100 Volts conforming to IS: 694:2010					
Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	(Price in Rs./100m)		(Price in Rs./100m)					
			Single Core	Packing	2 Core	3 Core	4 Core	2 - 4 Core Packing	5 Core	6 Core
0.5	16/.2	5	1400	24	3780	5090	6455	5	8000	9555
0.75	24/.2	8	1965	24	5035	6865	8755	5	11300	13625
1	32/.2	13	2470	20	6310	8695	11140	5	14550	17500
1.5	30/.25	17	3545	16	8555	12025	15530	5	19900	24200
2.5	50/.25	24	5870	12	13800	19100	25200	4	32400	39200
4	56/.3	30	8940	8	20500	29300	38400		51300	61400
6	84/.3	38	13415	6	30000	43000	56200		75600	90700
10	80/.4	52	23800	1	51000	74000	97800		130400	
16	126/.4	70	36900	1	80400	117200	154200		200200	
25	196/.4	88	57800	1	133300	193800	253400		363600	
35	276/.4	110	80800	1	185600	269300	354500		498300	
50	396/.4	145	115100	1	263500	383700	506500		721300	
70	354/.5	215	162900	1	374100	532100	703700		986400	
95	484/.5	260	214900	1		754300	995100			
120	608/.5	305	276400	1		957700	1264100			
150	750/.5	355	346500	1		1197200	1580300			
185	925/.5	415	430700	1		1474400	1948800			
240	1210/.5	500	562500	1		1903300	2519400			
300	1527/.5	585	704000	1		2375000	3145000			
400	2036/.5	695	937900	1		3164500	4165800			
500			1173300	1						
630			1513300	1						

POLYCAB BUILDING MANAGEMENT SYSTEM CABLES (BMS)						Polycab 90 Mtr. Single Core		Submersible/3CF Cable
Flexible Bare Copper Conductor, PVC Insulated, Cross Laid Up, Overall Aluminium Mylar Tape Shielded along with ATC Drain Wire PVC Outer Sheath BMS Cables (Price in Rs./100m)						Size (sq.mm.)	FR LF	FLAT CABLE
Cores	0.5 sq.mm	0.75 sq.mm	1.0 sq.mm	1.5 sq.mm	2.5 sq.mm		90 Mtrs.	
2	5945	7600	9130	11900	18600	0.75	1440	
3	7375	10010	12100	16100	25700	1	1940	
4	9130	12100	15500	20700	32500	1.5	2840	9840
5	11250	15100	18400	25100	41100	2.5	4490	15270
6	13000	17100	21400	30300	49200	4	6565	22500
7	14200	20100	24900	34000	58300	6	9810	33200
8	16100	21700	27700	38100	65000	10		57800
10	19100	26900	34000	47100	79500	16		89400
12	22600	31500	40200	55800	97500	25		140000
14	26300	36800	46500	64200		35		193500
16	29700	41300	52300	74100				
19	34000	49200	61800	86200				
24	42300	60400	76500	110000				



POLYCAB

IDEAS. CONNECTED.

**A B Pal Electricals (P) Limited****Price List**

LDC LP No. 10/2024-25 Dtd : 15th October 2024

Polycab PVC Insulated, FRLS Round Sheathed Multi Core Industrial Flexible Cables conforming to IS 694:2010 with Bright Annealed Copper Conductor for Voltage Grade 1100 Volts						
Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Price in Rs./100 Mtrs.			
			7 Core	8 Core	10 Core	12 Core
0.5	16/.2	5	10700	12700	15800	18600
0.75	24/.2	8	15250	17900	22500	26200
1	32/.2	13	19800	23000	28650	33900
1.5	30/.25	17	27300	31500	40100	47200
2.5	50/.25	24	44900	53300	65500	78700
4	56/.3	30	74000			
Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Price in Rs./100 Mtrs.			
			14 Core	16 Core	19 Core	24 Core
0.5	16/.2	5	21325	24300	28100	35500
0.75	24/.2	8	30750	34700	41000	51200
1	32/.2	13	39450	45000	52900	66300
1.5	30/.25	17	55900	64400	74800	95800
2.5	50/.25	24	91400	104400	121000	156700

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Core/Pair/Triad/Quad laid up together with Al (Inner sheathed GI Steel Wire Mylar/Drain Wire)
Round/Strip Armoured PVC Outer Sheathed Instrumentation

OVERALL SHIELDED - ARMOURED INSTRUMENTATION CABLES

Type	No.	Size	Rate/mtr	Size	Rate/mtr	Size	Rate/mtr	Size	Rate/mtr	Size	Rate/mtr
CORE	2	0.5	134	0.75	156	1	174	1.5	208	2.5	285
CORE	3	0.5	160	0.75	194	1	219	1.5	271	2.5	376
CORE	4	0.5	180	0.75	216	1	254	1.5	317	2.5	456
CORE	5	0.5	201	0.75	250	1	295	1.5	376	2.5	547
CORE	6	0.5	228	0.75	285	1	342	1.5	437	2.5	658
CORE	7	0.5	247	0.75	314	1	380	1.5	494	2.5	741
CORE	8	0.5	275	0.75	351	1	424	1.5	558	2.5	833
CORE	10	0.5	320	0.75	418	1	513	1.5	678	2.5	1032
CORE	12	0.5	359	0.75	475	1	581	1.5	780	2.5	1164
CORE	14	0.5	413	0.75	531	1	666	1.5	917	2.5	1376
CORE	16	0.5	454	0.75	599	1	746	1.5	1015	2.5	1551
CORE	19	0.5	510	0.75	677	1	859	1.5	1161	2.5	1822
CORE	24	0.5	617	0.75	851	1	1043	1.5	1437	2.5	2288

