

POLYCAB

IDEAS. CONNECTED.

**A B Pal Electricals (P) Limited****Price List**

LDC LP No. 11/2024-25 Dtd : 20th November 2024

Polycab PVC Insulated, PVC Round Sheathed Multi Core Industrial Flexible Cables conforming to IS 694:2010 with Bright Annealed Copper Conductor for Voltage Grade 1100 Volts

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Price in Rs./100 Mtrs.			
			7 Core	8 Core	10 Core	12 Core
0.5	16/.2	5	10250	12300	15200	17700
0.75	24/.2	8	14700	17300	21400	25200
1	32/.2	13	18700	22100	27300	32300
1.5	30/.25	17	26300	30200	38300	45200
2.5	50/.25	24	42600	50900	62800	75600
4	56/.3	30	70600			

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Price in Rs./100 Mtrs.			
			14 Core	16 Core	19 Core	24 Core
0.5	16/.2	5	20400	23200	27000	34000
0.75	24/.2	8	29300	33300	39100	48800
1	32/.2	13	37800	43000	50400	63400
1.5	30/.25	17	53500	61800	71500	91400
2.5	50/.25	24	87200	99700	115700	149600

COAXIAL CABLE	
	305M UNARMoured
RG 59	7030
RG 6	8860
RG 11	20185
RG 6 CCS	5700
RG 11 CCS	11505

TELEPHONE CABLE	
	0.5MM - 90MTR
1 PAIR	960
2 PAIR	1710
3 PAIR	2530
4 PAIR	3345
5 PAIR	4150
10 PAIR	8065
20 PAIR	15565

SPEAKER WIRE	
	90 MTR
0.5 SQ MM	1940
0.75 SQ MM	2815
1 SQ MM	3475
1.5 SQ MM	5170
2 SQ MM	7995
2.5 SQ MM	8580

OFC CABLE	
	SALE PRICE
6F SM UNITUBE ARMoured OFC CABLE	24
8F SM UNITUBE ARMoured OFC CABLE	27
12F UNITUBE ARMoured OFC CABLE	28

CCTV CABLE (90 MTR)	
CCTV 3+1	3785
CCTV 4+1	4115

LINE CABLE	
CAT 6 FTP FR PVC	12970



POLYCAB

IDEAS. CONNECTED.

**A B Pal Electricals (P) Limited****Price List**

LDC LP No. 11/2024-25 Dtd : 20th November 2024

Polycab FRLS Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:2010 with Bright Annealed Copper Conductor for Voltage Grade 1100 Volts					Polycab PVC Insulated and FRLS Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Flexible Cables for Voltage Grade 1100 Volts conforming to IS: 694:2010					
Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	(Price in Rs./100m)		(Price in Rs./100m)					
			Single Core	Packing	2 Core	3 Core	4 Core	2 - 4 Core Packing	5 Core	6 Core
0.5	16/.2	5	1365	24	3685	4965	6295	5	7800	9315
0.75	24/.2	8	1915	24	4910	6695	8535	5	11025	13300
1	32/.2	13	2410	20	6155	8480	10875	5	14200	17100
1.5	30/.25	17	3455	16	8340	11725	15150	5	19400	23600
2.5	50/.25	24	5725	12	13500	18600	24600	4	31600	38200
4	56/.3	30	8720	8	20000	28600	37400		50000	59900
6	84/.3	38	13100	6	29300	41900	54800		73700	88400
10	80/.4	52	23200	1	49700	72200	95400		127100	
16	126/.4	70	36000	1	78400	114300	150300		195200	
25	196/.4	88	56400	1	130000	189000	247100		354500	
35	276/.4	110	78800	1	181000	262600	345600		485800	
50	396/.4	145	112200	1	256900	374100	493800		703300	
70	354/.5	215	158800	1	364700	518800	686100		961700	
95	484/.5	260	209500	1		735400	970200			
120	608/.5	305	269500	1		933800	1232500			
150	750/.5	355	337800	1		1167300	1540800			
185	925/.5	415	419900	1		1437500	1900100			
240	1210/.5	500	548400	1		1855700	2456400			
300	1527/.5	585	686400	1		2315600	3066400			
400	2036/.5	695	914500	1		3085400	4061700			
500			1144000	1						
630			1475500	1						

POLYCAB BUILDING MANAGEMENT SYSTEM CABLES (BMS)						Polycab 90 Mtr. Single Core		Submersible/3CF Cable
Flexible Bare Copper Conductor, PVC Insulated, Cross Laid Up, Overall Aluminium Mylar Tape Shielded along with ATC Drain Wire PVC Outer Sheath BMS Cables (Price in Rs./100m)						Size (sq.mm.)	FR LF	FLAT CABLE
Cores	0.5 sq.mm	0.75 sq.mm	1.0 sq.mm	1.5 sq.mm	2.5 sq.mm		90 Mtrs.	
2	5800	7425	8905	11605	18150	0.75	1405	
3	7190	9775	11800	15700	25100	1	1890	
4	8900	11800	15125	21200	31700	1.5	2770	9530
5	11000	14700	17900	24500	40100	2.5	4375	14785
6	12700	16700	20900	29500	48000	4	6400	22115
7	13800	19600	24300	33200	56800	6	9565	32430
8	15700	21200	27000	37100	63400	10		56355
10	18600	26200	33200	45900	77500	16		87520
12	22000	30700	39200	54400	95100	25		136825
14	25600	35900	45300	62600		35		189595
16	29000	40300	51000	72200				
19	33200	48000	60300	84000				
24	41200	58900	74600	107300				



POLYCAB

IDEAS. CONNECTED.

**A B Pal Electricals (P) Limited****Price List**

LDC LP No. 11/2024-25 Dtd : 20th November 2024

Polycab PVC Insulated, FRLS Round Sheathed Multi Core Industrial Flexible Cables conforming to IS 694:2010 with Bright Annealed Copper Conductor for Voltage Grade 1100 Volts						
Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Price in Rs./100 Mtrs.			
			7 Core	8 Core	10 Core	12 Core
0.5	16/.2	5	10450	12400	15400	18100
0.75	24/.2	8	14900	17500	21900	25500
1	32/.2	13	19300	22400	27900	33100
1.5	30/.25	17	26600	30700	39100	46000
2.5	50/.25	24	43800	52000	63900	76700
4	56/.3	30	72200			
Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Price in Rs./100 Mtrs.			
			14 Core	16 Core	19 Core	24 Core
0.5	16/.2	5	20800	23700	27400	34600
0.75	24/.2	8	30000	33800	40000	49900
1	32/.2	13	38500	43900	51600	64600
1.5	30/.25	17	54500	62800	72900	93400
2.5	50/.25	24	89100	101800	118000	152800

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Core/Pair/Triad/Quad laid up together with Al (Inner sheathed GI Steel Wire Mylar/Drain Wire)
Round/Strip Armoured PVC Outer Sheathed Instrumentation

OVERALL SHIELDED - ARMOURED INSTRUMENTATION CABLES

Type	No.	Size	Rate/mtr	Size	Rate/mtr	Size	Rate/mtr	Size	Rate/mtr	Size	Rate/mtr
CORE	2	0.5	134	0.75	156	1	174	1.5	208	2.5	285
CORE	3	0.5	160	0.75	194	1	219	1.5	271	2.5	376
CORE	4	0.5	180	0.75	216	1	254	1.5	317	2.5	456
CORE	5	0.5	201	0.75	250	1	295	1.5	376	2.5	547
CORE	6	0.5	228	0.75	285	1	342	1.5	437	2.5	658
CORE	7	0.5	247	0.75	314	1	380	1.5	494	2.5	741
CORE	8	0.5	275	0.75	351	1	424	1.5	558	2.5	833
CORE	10	0.5	320	0.75	418	1	513	1.5	678	2.5	1032
CORE	12	0.5	359	0.75	475	1	581	1.5	780	2.5	1164
CORE	14	0.5	413	0.75	531	1	666	1.5	917	2.5	1376
CORE	16	0.5	454	0.75	599	1	746	1.5	1015	2.5	1551
CORE	19	0.5	510	0.75	677	1	859	1.5	1161	2.5	1822
CORE	24	0.5	617	0.75	851	1	1043	1.5	1437	2.5	2288

